

E1600 E75

TECHNICAL CATALOGUE

SLIDING WINDOW AND DOOR SYSTEM
WITH THERMAL BREAK

ES70 Q72

E75

E68

E45

ES38

EW70

Q60

E8000



ES70

WINDOW AND DOOR SYSTEM WITH THERMAL BREAK

TABLE OF CONTENTS

GENERAL INFORMATION	page 9
BUILDING PHYSICS	page 15
TABLES	page 21
PROFILES	page 25
SECTIONS	page 45
GLAZING OPTIONS	page 71
CUTTING LISTS	page 75
MACHINING	page 95
ACCESSORIES	page 139
CE MARKING	page 175

ETEM HISTORY

ETEM is a leading aluminium extrusion company. It was founded in 1971 as a part of the largest metal manufacturing holding in the Balkans. With over 40 years of experience ETEM is a fully integrated designer and producer of architectural systems and aluminium profiles for industrial applications.

Our mission is to listen and promptly respond to our customers' requests and design and manufacture aluminium products and systems, taking into consideration technical and aesthetic requirements.

ETEM focuses on sustainable development and has proven its concern about the protection of the natural environment by making considerable investments in anti-pollution measures and by optimizing production processes following the applicable standards of the European Union.

SERVICES WE PROVIDE

ETEM supports you with the following:

- ▷ design of conventional and bespoke architectural system solutions
- ▷ innovative engineering in the field of curtain walls, ventilated facades, doors, windows
- ▷ professional consultation and adequate technical advices ensured by our engineering team with wide experience in the field of profile extrusion as well as architectural systems' engineering

- ▷ reliable customer care constant support trainings, technical support and audits on site
- ▷ high quality engineering which guarantees offering the best solution according to the specific features of every single project
- ▷ managing the process of certification in accordance with the applicable European standards in Notified Bodies
- ▷ production of non-standard length profiles and non-standard processing high quality powder coating

ETEM PRODUCTS AND SUSTAINABLE DEVELOPMENT

SUSTAINABLE DEVELOPMENT IS DEVELOPMENT THAT MEETS THE NEEDS OF THE PRESENT WITHOUT COMPROMISING THE ABILITY OF FUTURE GENERATIONS TO MEET THEIR OWN NEEDS.*

For many, sustainable development is about environmental conservation. This is true but it also includes two other aspects: a social aspect and an economic aspect.

Sustainable development means striking the right balance between economic development, social equity and environmental protection.


For us meeting this objective translates into the challenge of satisfying market demands at the lowest economic, social and environmental cost possible.

ETEM has always designed architectural systems which are in compliance with all requirements for achieving high energy efficiency.

In order to assure the comfort of the building inhabitants, ETEM systems adapt their functions to the changing environment.

As a moderator between outside and inside our systems provide:


- › ENERGY EFFICIENCY
- › DAYLIGHT
- › SUN-SHADING
- › VENTILATION AND GOOD AIR QUALITY
- › SAFETY AND SECURITY



* Extract from Brundtland Report, from the United Nations World Commission on Environment and Development WCED

GENERAL INFORMATION

CONCEPT / ADVANTAGES / CERTIFICATES



ES70 WINDOW CONCEPT

ES70 IS A HIGH-END SLIDING WINDOW SYSTEM WITH THERMAL BREAK, SUITABLE FOR OPPOSED BALCONY DOORS AND WINDOWS WITH HIGH REQUIREMENTS FOR THERMAL INSULATION, FUNCTIONALITY AND AESTHETICS.

- Elegant straight design
- Excellent water-tightness and air-permeability
- High thermal insulation
- Glazing sash with 70.0mm width allowing glass panel from 25.0 up to 52.0mm
- Ability of Slim Line Interlock
- Maximum weight per sash 400 kg.

COMPLIANCE WITH APPLICABLE REGULATIONS

Production management

Quality Management system is certified in accordance with EN ISO 9001:2008.

Environmental management system is certified in accordance with EN ISO 14001.

Factory production control system is certified according to the requirements of EN 15088. All ETEM profiles are CE marked and in compliance with applicable European Standards.

ETEM is authorized to use the QUALICOAT quality sign for paint, lacquer and powder coating on aluminium for architectural applications.

Occupational Health & Safety Management System is certified in accordance with OHSAS 18001.

PERFORMANCE CHARACTERISTICS OF ES70

Characteristic	Classification / value	Standard
Air permeability	Up to class 4	EN 1026 / EN 12207
Watertightness	Up to class E900	EN 1027 / EN 12208
Resistance to wind load	Up to class C5	EN 12211 / EN 12210
Thermal transmittance	from 2,73 W/m ² K	EN ISO 10077-2

CLASSIFICATION OF CHARACTERISTICS

for windows without resistance to fire and/or smoke leakage characteristics according to EN 14351-1

Characteristic / value / dimension	Classification / Value										
Resistance to wind load Test pressure P1 (Pa)	npd	1 (400)	2 (800)	3 (1200)	4 (1600)	5 (2000)	Exxxx (>2000)				
Resistance to wind load Frame deflection	npd	A (≤1/150)	B (≤1/200)	C (≤1/300)							
Resistance to snow and permanent load	npd	Declared information on the infill (e.g. type and thickness of glass)									
Reaction to fire	npd	F	E	D	C	B	A2 A1				
External fire performance	npd	According to EN 13501-5									
Watertightness Non-shielded (A) Test pressure (Pa)		1A (0)	2A (50)	3A (100)	4A (150)	5A (200)	6A (250)	7A (300)	8A (450)	9A (600)	Exxxx (>600)
Watertightness Shielded (B) Test pressure (Pa)	npd	1B (0)	2B (50)	3B (100)	4B (150)	5B (200)	6B (250)	7B (300)			
Dangerous substances	npd	As required by regulations									
Impact resistance Drop height (mm)	npd	200	300	450	700	950					
Load-bearing capacity of safety devices	npd ^a	Threshold value									
Acoustic performance Sound insulation R _w (C;C _{tr}) (dB)	npd	Declared values									
Thermal transmittance U _w (W/(m ² .K))	npd	Declared values									
Radiation properties Solar factor (g)	npd	Declared values									
Radiation properties Light transmittance (τ _v)	npd	Declared values									
Air permeability Max. test pressure (Pa) Reference air permeability at 100 Pa (m ³ /(h · m ²) or m ³ /(h · m))	npd	1 (150)	2 (300)	3 (600)	4 (600)						
Operating forces ^b	npd	1	2								
Mechanical strength	npd	1	2	3	4						
Ventilation		Declared values									
Air flow exponent n Air flow characteristic K Air flow rates	npd										
Bullet resistance	npd	FB1	FB2	FB3	FB4	FB5	FB6	FB7	FSG		
Explosion resistance Shock tube	npd	EPR1		EPR2		EPR3		EPR4			
Explosion resistance Range test	npd	EXR1		EXR2		EXR3		EXR4		EXR5	
Resistance to repeated opening and closing Number of cycles	npd	5000		10 000		20 000					
Behaviour between different climates	npd	Under development									
Burglar resistance	npd	1	2	3	4	5	6				

NOTE 1: npd: no performance determined

NOTE 2: The figures in brackets are for information

^a Only if safety device(s) is(are) not provided

^b Manually operated windows only

BUILDING PHYSICS

DIMENSIONING / FORMULAS / EXAMPLES

ALUMINIUM AS MATERIAL

ALUMINIUM IS A VERY YOUNG METAL, EXTRACTED FOR THE FIRST TIME IN 1854. COMMERCIALLY PRODUCED AS A PRECIOUS METAL FROM 1886, ITS INDUSTRIAL PRODUCTION FOR CIVIL APPLICATIONS ONLY ACHIEVED WIDE USE IN THE 1950'S.

NOW ALUMINIUM PLAYS A KEY ROLE FOR THE SUSTAINABILITY OF NEW BUILDINGS AND THE RENOVATION OF EXISTING ONES. THANKS TO ITS PERFORMANCE PROPERTIES ALUMINIUM CONTRIBUTES TO THE ENERGY PERFORMANCE, SAFETY AND COMFORT OF NEW BUILDINGS.

ADVANTAGES

DESIGN FLEXIBILITY

The extrusion process offers an almost infinite range of forms and sections, allowing designers to integrate numerous functions into one profile

LONG SERVICE LIFE

Aluminium building products are made from alloys that are weatherproof, corrosion-resistant and immune to the harmful effects of UV rays, ensuring optimal performance over a very long period of time

HIGH STRENGTH-TO-WEIGHT RATIO

Thanks to the metal's inherent strength and stiffness, aluminium window and curtain wall frames can be very narrow. Material's light weight makes it easier to transport and handle on-site, reducing the risk of work-related injury

HIGH-REFLECTIVITY

This characteristic feature makes aluminium a very efficient material for light management. Aluminium shading devices can be used to reduce the need for air conditioning in summer

FIRE SAFETY

Aluminium does not burn and therefore is classified as a non-combustible construction material (European Fire Class A1). Aluminium alloys will nevertheless melt at around 6500 C, but without releasing harmful gases

NO RELEASE OF DANGEROUS SUBSTANCES

Several studies have proved that aluminium building products do not present a hazard to occupants or the surrounding environment. Aluminium building products have no negative impact, either on indoor air quality or on soil, surface and groundwater

OPTIMAL SECURITY

Where high security is required, specially designed, strengthened aluminium frames can be used. While the glass for such applications may well be heavy, the overall weight of the structure remains manageable thanks to the light weight of the aluminium frames.

ALLOYS

Aluminium in its pure form is a very soft metal. Thanks to the addition of alloying elements such as copper, manganese, magnesium, zinc, etc. and thanks to suitable production processes, the physical and mechanical properties can be varied in a wide range to satisfy the requirements of a large number of different applications.

The most common aluminium alloy which is used by ETEM is EN AW 6063. Here are the properties of this alloy:

MATERIAL PROPERTIES

Aluminium alloy	EN F22
Ultimate tensile strength	$R_m = 210 \text{ N/mm}^2$
Yield strength	$R_{p_0,2} = 160 \text{ N/mm}^2$
Modulus of elasticity	$E_{al}=70\ 000 \text{ N/mm}^2 = 7.10^9 \text{ kg/m}^2$
Coefficient of thermal expansion	$\alpha=0.023 \text{ mm/m .K}$ (up to 12 mm/m for difference up to 50°C)

EXTRUSION PROCESS

ETEM profiles are obtained through extrusion process, which consists of pushing a hot cylindrical bullet of aluminium through a shaped die. The extrusion process offers almost infinite range of forms and sections, allowing our designers to integrate numerous functions into one single profile.

aluminium surface, increasing hardness, corrosion and abrasion resistance. Anodizing gives a very decorative silver matt surface finish, and colored can also be obtained by sealing metallic dyes into the anodized layer.

FINISHING

POWDER COATING

It is a type of paint that is applied as a dry powder. Coating is applied on ETEM profiles electrostatically and then is cured under heat to allow it to flow and form a "skin".

ETEM is authorized to use the quality sign QUALICOAT for powder coatings on aluminium for architectural applications. A wide range of colors and gloss levels can be achieved.

ETEM also offers timber imitations painting, in addition to all RAL colors. The technology EZY provides the following colors: Golden Oak, Acer, Betulla, Mogano, Verde Scuro, Wenge, Noce Fiammato, Noce Chiaro, Ciliegio Rosso, Acacia Scuro, Ciliegio Antico, Noce Reale, Ciliegio Reale.

ANODIZING

It is an electrochemical process whereby to reinforce the natural oxide film on the

MAINTENANCE

Apart from routine cleaning for aesthetic reasons, ETEM aluminium profiles do not require any maintenance which translates into a major cost and ecological advantage over lifetime of the product.

RECYCLING

Aluminium scrap can be repeatedly recycled without any loss of value or properties. In many instances, aluminium is combined with other materials such as steel or plastics, which are most frequently mechanically separated from aluminium before being molten.

CALCULATION OF GLASS PANE THICKNESS

*Glazing thickness:


For single glazing the minimum thickness is given by the following equations:

$$\text{a) If } \frac{h_g}{l_g} \leq 3, \quad t = \sqrt{\frac{10 \cdot l_g \cdot h_g \cdot w}{72}}, \text{ mm}$$

or

$$\text{b) If } \frac{h_g}{l_g} > 3, \quad t = \frac{l_g \cdot \sqrt{10 \cdot w}}{72}, \text{ mm}$$

Example:



Where:

t - Minimum theoretical glass thickness, mm

w - Wind pressure, kg/m²

l_g - The smallest dimension of the glass pane, m

h_g - The largest dimension of the glass pane, m

For double glazing, the total thickness of both glasses in the panel is equal to the thickness of a single glass pane (evaluated using the above equations) multiplied by 1.5

For triple glazing, the total thickness of all glasses in the panel is equal to the thickness of a single glass pane (evaluated using the above equations) multiplied by 1.7

Always consult facade engineer or glazing manufacturer when calculating for required glazing thickness and maximum allowable dimensions.

Initial data:

$$l_g = 1,5 \text{ m}$$

$$h_g = 2,0 \text{ m}$$

$$w = 60 \text{ kg/m}^2$$

$$\frac{h_g}{l_g} = \frac{2}{1,5} = 1,33 \leq 3$$

$$t = \sqrt{\frac{10 \cdot l_g \cdot h_g \cdot w}{72}} = \sqrt{\frac{10 \cdot 1,5 \cdot 2 \cdot 60}{72}} = \sqrt{\frac{1800}{72}} = 5 \text{ mm}$$

For double glazing $t_{req} = 1,5 \cdot 5 = 7,5 \text{ mm}$













We choose double glazing 5/14/5

TABLES

TYPOLOGIES / LIST OF PROFILES / CHARACTERISTICS

sliding system with thermal break

ES70



PROFILES

DRAWINGS / SCALE 1:1

sliding system with thermal break

ES70

code	profile	weight length moment of inertia	code	profile	weight length moment of inertia
E6270103 Double rail		2711 g/m L=6.01 m	E6270131 Additional flat rail		1510 g/m L=6.01 m
E6270104 Triple rail		3356 g/m L=6.01 m	E6270132 Additional flat rail for fly screen		616 g/m L=6.01 m
E6270105 Internal part of triple - multi rail		2549 g/m L=6.01 m	E6270150 Hotel type rail		2731 g/m L=6.01 m
E6270106 Additinal for multi rail		1377 g/m L=6.01 m	E6270201 Glazing sash		2676 g/m L=6.01 m $J_x=63.7 \text{ cm}^4$ $J_y=69.4 \text{ cm}^4$
E6270107 Additional part for triple - multi rail		1553 g/m L=6.01 m	E6270250 Narrow sash interlock		1540 g/m L=6.01 m $J_x=4.5 \text{ cm}^4$ $J_y=33.0 \text{ cm}^4$
E6270130 Double flat rail		2574 g/m L=6.01 m	E6270350 Hotel type mullion		3087 g/m L=6.01 m $J_x=69.0 \text{ cm}^4$ $J_y=71.1 \text{ cm}^4$

sliding system with thermal break

ES70

code	profile	weight length moment of inertia	code	profile	weight length moment of inertia
E6270520 Adjoining corner profile for 90°		2511 g/m L=6.01 m $J_x = 31.3 \text{ cm}^4$ $J_y = 98.5 \text{ cm}^4$	E6270681 Glazing bead		284 g/m L=6.01 m
E6270510 Adjoining profile		1255 g/m L=6.01 m $J_x = 20.9 \text{ cm}^4$ $J_y = 2.0 \text{ cm}^4$	E6270682 Glazing bead		300 g/m L=6.01 m
E6270501 Interlock profile		456 g/m L=6.01 m	E6270683 Glazing bead		340 g/m L=6.01 m
E6270650 Hotel type cap		535 g/m L=6.01 m	E6270684 Glazing bead		328 g/m L=6.01 m
E6270620 Drip profile		410 g/m L=6.01 m	E6270690 Connector for slide-fixed		2016 g/m L=6.01 m $J_x = 7.5 \text{ cm}^4$ $J_y = 206.5 \text{ cm}^4$
E6270680 Glazing bead		215 g/m L=6.01 m	E6270695 Length connector for E50 & ES70		224 g/m L=6.01 m

ES70L-02

sliding system with thermal break

ES70

code	profile	weight length moment of inertia	code	profile	weight length moment of inertia
E6270902 Connecting rod		389 g/m L=6.01 m	E22214 Fly-screen sash		857 g/m L=6.01 m
E6270904 Connecting rod (for narrow sash)		186 g/m L=6.01 m	E22215 "T" profile for fly screen		591 g/m L=6.01 m
E22216 Vertical screen sash		732 g/m L=6.01 m	E19651 Cover for fly screen		100 g/m L=6.01 m
E22216 Cover for fly screen		105 g/m L=6.01 m	E6270220 Screen sash for flat rails E50 & ES70		1112 g/m L=6.01 m
E50901W1 Aluminium drainage grill (available only perforated)		124 g/m L=6.01 m			

ES70L-03


sliding system with thermal break

ES70

E6270103

Double rail

2711 g/m



scale : 1:1


sliding system with thermal break

ES70

E6270104

Triple rail

3356 g/m




scale : 1:1

sliding system with thermal break

ES70

E6270105


Internal part of triple
- multi rail



E6270106

Additional rail for
multiple frames

1377 g/m



scale : 1:1

ES70 P-03


sliding system with thermal break

ES70

E6270107

Additional part for
triple - multi rail


1553 g/m



E6270130

Double flat rail

2574 g/m



scale : 1:1

ES70 P-04


sliding system with thermal break

ES70

E6270131

Additional flat rail


1510 g/m



E6270132

Additional flat rail
for fly screen

616 g/m



scale : 1:1


sliding system with thermal break

ES70

E6270201

Glazing sash


2676 g/m



E6270250

Narrow sash interlock


1540 g/m



scale : 1:1

sliding system with thermal break


ES70



E6270150

Hotel type rail

2731 g/m



scale : 1:1


sliding system with thermal break

ES70

E6270510

Adjoining profile


1255 g/m



E6270501

Interlock profile

456 g/m




scale : 1:1

sliding system with thermal break**ES70**

E6270520

Adjoining corner
profile for 90°

2511 g/m



scale : 1:1


ES70.P-09

sliding system with thermal break**ES70**

E6270650

Hotel type cap


535 g/m



E6270620

Drip profile


410 g/m



E6270695

Length connector for
E50 & ES70

224 g/m



scale : 1:1


ES70.P-010

sliding system with thermal break**ES70**

E6270680

Glazing bead


215 g/m



E6270681

Glazing bead


284 g/m



E6270682

Glazing bead


300 g/m

**sliding system with thermal break****ES70**

E6270690

Connector for
slide-fixed


2016 g/m



E6270684

Glazing bead


328 g/m



E6270683

Glazing bead

340 g/m



scale : 1:1

scale : 1:1


sliding system with thermal break

ES70

E50901W1

Aluminium drainage grill
(available only perforated)


124 g/m



E6270220

Screen sash
for flat rail


1112 g/m



E6270902

Connecting rod


389 g/m



E6270904

Connecting rod
(for narrow sash)

186 g/m



ES70.P-013


scale : 1:1

sliding system with thermal break

ES70

E22214


Fly-screen sash
857 g/m



E22215

"T" profile
for fly screen


591 g/m



E22216

Vertical screen sash


732 g/m



E19651

Cover for fly screen


100 g/m



E22616

Cover for fly screen
E22216

105 g/m



ES70.P-014


scale : 1:1

SECTIONS

SECTIONS / DETAILS

sliding system with thermal break


ES70



sliding system with thermal break

ES70

CLASSIC INTERLOCK




scale : 1:1

sliding system with thermal break

ES70


SLIM INTERLOCK



scale : 1:1

sliding system with thermal break


ES70



scale : 1:1

sliding system with thermal break



ES70



scale : 1:1

sliding system with thermal break



ES70



scale : 1:1.5

sliding system with thermal break


ES70



scale : 1:1.5


sliding system with thermal break

ES70




sliding system with thermal break

ES70




sliding system with thermal break



100





System with thermal break

ES70



sliding system with thermal break**ES70**


scale : 1:1

sliding system with thermal break**ES70**


scale : 1:1

sliding system with thermal break


ES70




HOTEL TYPE

**sliding system with thermal break**

ES70




HOTEL TYPE




sliding system with thermal break

ES70



sliding system with thermal break


ES70



sliding system with thermal break

ES70


HOTEL TYPE



sliding system with thermal break


ES70

TRIPLE GLAZING




sliding system with thermal break

ES70




sliding system with thermal break

ES70



sliding system with thermal break

ES70



scale : 1:1


ES70 technical catalogue

68

ETEM

sliding system with thermal break

ES70








scale : 1:1

ES70 technical catalogue

69

ETEM

GLAZING OPTIONS

external gaskets	GLAZING OPTIONS				GLAZING BEADS
	INTERNAL GASKETS				
3 mm 130402	5 mm 130205	6 mm 130206	7 mm 130207	8 mm 130208	
X mm					
130402	52	51	50	49	E6270680 
130402	44	43	42	41	E6270681 
130402	39	38	37	36	E6270682 
130402	28	27	26	25	E6270683 
130402	34	33	32	31	E6270684 

Note:
Tolerance in dimension chain $\pm 0.5\text{mm}$


CUTTING LISTS

sliding system with thermal break

ES70


DOUBLE LEAF SLIDING WINDOW

ES70.T-01



CUTTING LENGTHS	
FRAME WIDTH	= W
FRAME HEIGHT	= H
SASH WIDTH	$\frac{(W+15)}{2}$
SASH HEIGHT	= H - 78
INTERLOCKING HEIGHT	= H - 98
DIMENSIONS IN MILLIMETERS	


no scale





sliding system with thermal break

ES70

DOUBLE LEAF SLIDING WINDOW WITH SLIM INTERLOCK



CUTTING LENGTHS	
FRAME WIDTH	= W
FRAME HEIGHT	= H
SASH WIDTH (SW)	= $\frac{(W+74)}{2}$
FINAL SASH WIDTH	= SW - 59
SASH HEIGHT	= H - 78
NARROW SASH HEIGHT (E6270250)	= H - 196
INTERLOCKING HEIGHT	= H - 98
DIMENSIONS IN MILLIMETERS	




sliding system with thermal break

ES70



ES70.T-02

DOUBLE LEAF SLIDING WINDOW WITH FLAT FRAME

ES70.T-03




CUTTING LENGTHS	
E6270103 FRAME WIDTH	= W
E6270130 FLAT FRAME WIDTH	= W-36*
E6270103 FRAME HEIGHT	= H
SASH WIDTH	= $\frac{(W+15)}{2}$
SASH HEIGHT	= H - 69
INTERLOCKING HEIGHT	= H - 89
DIMENSION IN MILLIMETERS	
*NOTE: CUTTING LENGTH INCLUDE FLANGE THICKNESS (ET076679.00)	



sliding system with thermal break

ES70


DOUBLE LEAF SLIDING WINDOW WITH FLYSCREEN




CUTTING LENGTHS	
FRAME WIDTH	= W
FRAME HEIGHT	= H
SASH WIDTH	$\frac{(W+15)}{2}$
SASH HEIGHT	$H - 78$
FLYSCREEN WIDTH	$\frac{(W-41)}{2}$
FLYSCREEN HEIGHT	$H - 78$
INTERLOCKING HEIGHT	$H - 98$
DIMENSIONS IN MILLIMETERS	

ES70.T-04
Vertical sect.

no scale



(1)



(2)


2 | 10 | 50 | mm
0.01 | 0.15 | 2.0 | 100 |

sliding system with thermal break




ES70

DOUBLE LEAF SLIDING WINDOW WITH FLYSCREEN

ES70.T-04
Horizontal sect.



CUTTING LENGTHS	
FRAME WIDTH	= W
FRAME HEIGHT	= H
SASH WIDTH	$\frac{(W+15)}{2}$
SASH HEIGHT	$H - 78$
FLYSCREEN WIDTH	$\frac{(W-41)}{2}$
FLYSCREEN HEIGHT	$H - 78$
INTERLOCKING HEIGHT	$H - 98$
DIMENSIONS IN MILLIMETERS	




no scale


sliding system with thermal break

ES70

DOUBLE LEAF SLIDING WINDOW WITH FLY SCREEN - FLAT FRAME



CUTTING LENGTHS	
E6270104 FRAME WIDTH	= W
E6270130 & E6270132 FLAT FRAMES WIDTH	= W-36*
E6270104 FRAME HEIGHT	= H
SASH WIDTH	= $\frac{(W+15)}{2}$
SASH HEIGHT	= H - 69
INTERLOCKING HEIGHT	= H - 89
WIDTH OF SCREEN SASH E6270220	= $\frac{(W-61)}{2}$
HEIGHT OF SCREEN SASH E6270220	= H - 69
DIMENSION IN MILLIMETERS	
* NOTE: CUTTING LENGTH INCLUDE FLANGE THICKNESS (ET076701.00)	




no scale


sliding system with thermal break

ES70

DOUBLE LEAF SLIDING WINDOW WITH FLY SCREEN - FLAT FRAME



CUTTING LENGTHS	
E6270104 FRAME WIDTH	= W
E6270130 & E6270132 FLAT FRAMES WIDTH	= W-36*
E6270104 FRAME HEIGHT	= H
SASH WIDTH	= $\frac{(W+15)}{2}$
SASH HEIGHT	= H - 69
INTERLOCKING HEIGHT	= H - 89
WIDTH OF SCREEN SASH E6270220	= $\frac{(W-61)}{2}$
HEIGHT OF SCREEN SASH E6270220	= H - 69
DIMENSION IN MILLIMETERS	
* NOTE: CUTTING LENGTH INCLUDE FLANGE THICKNESS (ET076701.00)	




no scale

sliding system with thermal break

ES70


DOUBLE LEAF SLIDING WINDOW WITH FLY SCREEN - FLAT FRAME



sliding system with thermal break

ES70


DOUBLE LEAF SLIDING WINDOW WITH FLY SCREEN - FLAT FRAME



sliding system with thermal break

ES70


TRIPLE LEAF SLIDING WINDOW



sliding system with thermal break

ES70


TRIPLE LEAF SLIDING WINDOW



sliding system with thermal break


ES70

QUADRUPLE LEAF SLIDING WINDOW



CUTTING LENGTHS	
FRAME WIDTH	= W
FRAME HEIGHT	= H
SASH WIDTH	$\frac{(W+94)}{4}$
SASH HEIGHT	= H - 78
ADJOINING HEIGHT	= H - 121
INTERLOCKING HEIGHT	= H - 98
DIMENSIONS IN MILLIMETERS	

ES70.T-08
Vertical sect.




no scale

sliding system with thermal break

ES70

QUADRUPLE LEAF SLIDING WINDOW

ES70.T-08
Horizontal sect.




no scale


sliding system with thermal break

ES70

HOTEL TYPE (SLIM INTERLOCK)
LIFTING & SLIDING WINDOW - FIXED



CUTTING LENGTHS	
FRAME WIDTH	= W
FRAME HEIGHT	= H
SASH WIDTH (SW)	= $\frac{W}{2} + 75$
FINAL SASH WIDTH	= SW - 59
SASH HEIGHT (E6270201)	= H - 78
NARROW SASH HEIGHT (E6270250) (FOR SLIDING PART)	= H - 196
NARROW SASH HEIGHT (E6270250) (AS MULLION FOR FIXED)	= H - 48
E6270501 INTERLOCKING HEIGHT	= H - 98
E6270501 (FOR FIXED) INTERLOCKING HEIGHT	= H - 48
DIMENSIONS IN MILLIMETERS	



no scale


ES70

sliding system with thermal break




ES70

HOTEL TYPE (CLASSIC INTERLOCK)
LIFTING & SLIDING WINDOW - FIXED

ES70.T-010



CUTTING LENGTHS	
FRAME WIDTH	= W
FRAME HEIGHT	= H
SASH WIDTH	= $\frac{W}{2} + 45$
SASH HEIGHT	= H - 78
6270350 MULLION HEIGHT	= H - 48
6270501 INTERLOCKING HEIGHT	= H - 98
6270501 (FOR FIXED) INTERLOCKING HEIGHT	= H - 48
DIMENSIONS IN MILLIMETERS	




no scale

sliding system with thermal break


ES70

HOTEL TYPE (CLASSIC INTERLOCK)

FIXED - MEETING DOUBLE SASH LIFTING & SLIDING WINDOW - FIXED






CUTTING LENGTHS	
FRAME WIDTH	= W
FRAME HEIGHT	= H
SASH WIDTH	= $\frac{W}{4} + 63$
SASH HEIGHT	= H - 78
E6270350 MULLION HEIGHT	= H - 48
E6270501 INTERLOCKING HEIGHT	= H - 98
E6270501 (FOR FIXED) INTERLOCKING HEIGHT	= H - 48
E6270510 ADJOINING HEIGHT	= H - 121
DIMENSIONS IN MILLIMETERS	



no scale

ES70.T-011




mm

sliding system with thermal break



ES70

DOUBLE LEAF LIFT & SLIDE WITH 90° CORNER PROFILE

ES70.T-012



CUTTING LENGTHS	
WIDTH OF RAIL E6270103	= W
HEIGHT OF FRAME E6270103	= H
WS (WIDTH OF SASH)	= $\frac{W - 65}{2}$
HS (HEIGHT OF SASH)	= H - 78
HEIGHT OF SUPPL. E6070501	= H - 98
HEIGHT OF E6270520	= H - 88
DIMENSION IN MILLIMETERS	



mm

ES70 technical catalogue

93

MACHININGS


MACHININGS / PROCESSING

sliding system with thermal break

ES70

MACHINING ON RAIL FOR FIXING WITH DIE CAST JOINT CORNER BRACKETS

ES70.M-01




sliding system with thermal break

ES70

MACHINING ON RAIL FOR FIXING WITH EXTRUDED ALUM. JOINT CORNER BRACKETS

ES70.M-02




sliding system with thermal break

ES70

FIXING SASH FRAME WITH EXTRUDED ALUM. JOINT CORNER BRACKETS

ES70.M-03




sliding system with thermal break

ES70

MACHINING ON SASH PROFILE FOR FIXING WITH DIE CAST JOINT CORNER BRACKET

ES70.M-04




sliding system with thermal break

ES70

MACHINING ON HORIZ. SASH E6270201 FOR CONNECTION WITH NARROW SASH E6270250

ES70.M-05




sliding system with thermal break


ES70

MACHINING ON SASH PROFILE FOR DRAIN HOLES

ES70.M-06



THE DRAIN HOLES ARE OPENED
AT THE PUNCHING MACHINE




sliding system with thermal break

ES70

MACHINING ON FLY SCREEN FOR FIXING WITH DIE CAST JOINT CORNER BRACKET
& INSTRUCTIONS FOR CONNECTION WITH NARROW FLY SCREEN E22216


ES70.M-07



sliding system with thermal break

ES70

MACHINING OF INTERLOCK PROFILE E6270501




ES70.M-08

sliding system with thermal break

ES70

FIXING INTERLOCK PROFILE E6270501

ES70.M-09




PLUG ET.074786.00 IS FIXED ONTO THE BOTTOM SIDE OF INTERLOCK PROFILE E6270501, WHILST PLUG ET.074806.00 IS FIXED ONTO THE TOP SIDE

sliding system with thermal break


ES70

FIXING INTERLOCK PROFILE ONTO THE SASH FRAME


ES70.M-010




E6270501



PLASTIC SPACER ET080230.00 IS FIXED ONTO THE SASH FRAME USING SHEET METAL SCREWS 4.2x25mm DIN 7982C. THE FIRST SCREW IS FIXED AT A DISTANCE OF 20mm, MEASURED FOR THE ENDS OF PROFILE E6270501, AND THE CENTER TO CENTER DISTANCE BETWEEN THE NEXT SCREWS MUST BE APPROXIMATELY 250mm.



ET074811.00







FIX ON BOTH SIDES OF PLASTIC SPACER ET080230.00 THE PAIR OF PLASTIC PLUG ET074811.00. ALWAYS APPLY SILICON IN ADVANCE AT THE SURFACE WHERE THE PLUG IS TO BE FIXED

sliding system with thermal break

ES70

MACHINING OF INTERLOCK PROFILE FOR NARROW SASH FRAME

ES70.M-011




PLUG ET.074786.00 IS FIXED ONTO THE BOTTOM SIDE OF INTERLOCK PROFILE, WHILST PLUG ET.074806.00 IS FIXED ONTO THE TOP SIDE

FIX ON BOTH SIDES OF PLASTIC SPACER ET080233.00 THE PAIR OF PLASTIC PLUG ET074822.00. ALWAYS APPLY SILICON IN ADVANCE AT THE SURFACE WHERE THE PLUG IS TO BE FIXED

sliding system with thermal break

ES70

MACHINING REQUIRED FOR 90° CONNECTION OF RAILS




ES70.M-012

sliding system with thermal break

ES70

MACHINING REQUIRED FOR 90° CONNECTION OF RAILS




ES70 technical catalogue

ETEM

sliding system with thermal break

ES70

HANDLE MACHINING FOR SASH E6270201 (GU HARDWARE)




ES70.M-014

sliding system with thermal break

ES70


LIFT & SLIDE MECHANISM INSTALLATION ON SASH E6270201



sliding system with thermal break

ES70

HANDLE MACHINING FOR SASH E6270201 (GU HARDWARE) - ONLY FOR FLAT RAIL




ES70.M-016

sliding system with thermal break

ES70

LIFT & SLIDE MECHANISM INSTALLATION ON SASH E6270201 - ONLY FOR FLAT RAIL

ES70.M-017




sliding system with thermal break

ES70

FIXING RAIL WITH EXTRUDED ALUM. JOINT CORNER BRACKETS - HOTEL TYPE

ES70.M-018




sliding system with thermal break

ES70

MACHINING ON INTERLOCK PROFILE E6270501 - HOTEL TYPE


ES70.M-019



sliding system with thermal break

ES70

MACHINING ON MULLION E6270350 - HOTEL TYPE





ES70.M-020

sliding system with thermal break

ES70

INSTRUCTIONS FOR FITTING SEALING BLOCK - HOTEL TYPE


ES70.M-021



sliding system with thermal break



ES70

FIXING MULLION E6270350 - HOTEL TYPE



ES70.M-022

scale 1:1




sliding system with thermal break


ES70

FIXING SASH PROFILE E6270201 AS MULLION - HOTEL TYPE


ES70.M-023



1st STEP:
INSERT 2 PCS OF PROFILE
E6270902 INTO THE SASH.
FOR FIXING THEM, USE 4PCS OF
SCREWS ST4.8x32mm
DIN 7981C or DIN7982C





2nd STEP:
MILLING CUT



E6270201

3rd STEP:
FIXING ONTO THE RAIL




FOR FIXING, USE 4PCS OF
SCREWS ST4.8x45mm
DIN 7981C

sliding system with thermal break

ES70

FIXING SASH PROFILE E6270250 AS MULLION - HOTEL TYPE




ES70.M-024

sliding system with thermal break

ES70

INSTRUCTIONS FOR WATER DRAINAGE - HOTEL TYPE




sliding system with thermal break

ES70

INSTRUCTIONS FOR WATER DRAINAGE - HOTEL TYPE

ES70.M-026



122


ETEM

sliding system with thermal break

ES70

MACHINING ON DOUBLE RAIL E6270103 FOR DRAINAGE

ES70.M-027




123

ETEM

sliding system with thermal break


ES70

MACHINING ON DOUBLE RAIL E6270103 FOR DRAINAGE (REQUIRED FOR HIGH PERFORMANCES)



ES70.M-028


* THE DRAIN HOLE (30x5) IS PERFORMED
USING THE PUNCHING MACHINE



sliding system with thermal break

ES70


MACHINING ON FLAT RAIL E6270130 FOR DRAINAGE



sliding system with thermal break

ES70




MACHINING ON FLAT RAIL E6270130 FOR DRAINAGE



sliding system with thermal break

ES70


DRAINAGE MACHINING FOR TRIPLE & MULTIPLE RAIL



sliding system with thermal break

ES70

DRAINAGE MACHINING FOR TRIPLE & MULTIPLE RAIL




sliding system with thermal break

ES70

FIXING ADJOINING PROFILE E6270510



ES70.M-033



sliding system with thermal break

ES70

PVC INTERLOCK REINFORCEMENT APPLICATION



ES70


ES70.M-034

sliding system with thermal break


ES70

FRAME E6270103 ALIGNMENT & ASSEMBLY (FOR 90° CORNER)

ES70.M-035




ATTENTION: ALWAYS APPLY SEALANT AT THE JOINT BETWEEN THE PROFILES



sliding system with thermal break

ES70

MACHINING OF ADJ. PROFILE E6270520 FOR PLASTIC PLUGS INSTALLATION
(FOR 90° CORNER)



ES70.M-036

sliding system with thermal break


ES70

INSTALLATION OF E6270520 ANCHOR WITH LATCH ET055053.00 (FOR 90° CORNER)

ES70.M-037

Part of ET055053.00
Locking striker for 1st sliding sash

Part of ET055053.00
Latch for 2nd sliding sash






sliding system with thermal break

ES70

SELECTION OF GASKET & BRUSHES FOR ES70

ES70.M-038






A	ET 130048	
B	ET 130770	
C	ET 135506	
D	ET 130173	
E	ET 135508	
F	ET 130170	
G	ET 135514	
H	ET 130830	
I	ET 130112	
K	ET 130101	

sliding system with thermal break

ES70

SELECTION OF GASKET & BRUSHES FOR ES70

ES70.M-039





A	ET 130048	
B	ET 130770	
C	ET 135506	
D	ET 130173	
E	ET 135508	
F	ET 130170	
G	ET 135514	
H	ET 130830	
I	ET 130112	
K	ET 130101	

sliding system with thermal break


ES70

SELECTION OF GASKET & BRUSHES FOR ES70



A	ET 130048	
B	ET 130770	
C	ET 135506	6.0mm
D	ET 130173	
E	ET 135508	8.0mm
F	ET 130170	
G	ET 135514	14.0mm
H	ET 130830	
I	ET 130112	
K	ET 130101	



ES70.M-040



sliding system with thermal break

ES70

SELECTION OF GASKET & BRUSHES FOR ES70




A	ET 130048	
B	ET 130770	
C	ET 135506	6.0mm
D	ET 130173	
E	ET 135508	8.0mm
F	ET 130170	
G	ET 135514	14.0mm
H	ET 130830	
I	ET 130112	
K	ET 130101	
L	ET 135588	8.0mm (base 4.8mm)

ACCESSORIES

IMAGES / DESCRIPTIONS

code/description	package/pcs	colour
ET 130205.00		●

Glazing EPDM gasket
press-in 5.0 mm



ET 130206.00		●
--------------	--	---

Glazing EPDM gasket
press-in 6.0 mm



ET 130207.00		●
--------------	--	---

Glazing EPDM gasket
press-in 7.0 mm



ET 130208.00		●
--------------	--	---

Glazing EPDM gasket
press-in 8.0 mm




sliding system with thermal break

ES70


code/description	package/pcs	colour
ET 130407.00		●

Glazing EPDM gasket
press-in 5.0 mm




ET 130402.00		●
--------------	--	---

Elongated glazing EPDM
gasket 3.0mm




ET 130048.00		●
--------------	--	---

Frame gasket for sash



ET 130112.00		●
--------------	--	---

Sash gasket for low rail




sliding system with thermal break

ES70

code/description	package/pcs	colour
ET 130170.00		●

Groove cover gasket for
ES6270201



ET 130173.00		●
--------------	--	---

Stopper gasket for interlock
PVC ES70




ET 130770.00		●
--------------	--	---

EPDM gasket for rail groove
covering



ET 130830.00		●
--------------	--	---

EPDM gasket for adjoining
profile




sliding system with thermal break

ES70


code/description	package/pcs	colour
ET 130831.00		●

Wall-joining EPDM external gasket for straight fixed frame




ET 080751.00		●
--------------	--	---

Additional insulator for sash




ET 130101.00		●
--------------	--	---

EPDM foam gasket Ø4mm



ET 082201.00		
--------------	--	--

Stainless steel rail (E36, E50, ES70)




sliding system with thermal break

ES70


code/description	package/pcs	colour
ET 080213.00		●

Plastic profile (PVC) for sash 6070201




ET 080229.00		●
--------------	--	---

Plastic profile (PVC) for rails




ET 080232.00		●
--------------	--	---

Plastic profile (PVC) for hotel type rail



ET 080230.00		●
--------------	--	---

Plastic spacer for interlock for ES70




sliding system with thermal break

ES70


code/description	package/pcs	colour
ET 080231.00		●

Glazing sash internal PVC



ET 080233.00		●
--------------	--	---

Plastic profile (PVC) for slim interlock




ET 080234.00		●
--------------	--	---

Plastic profile (PVC) for hotel type rail cover



ET 135406.01		●
ET 135406.02		●
ET 135406.04		○

Pile weatherseal
4P 6.0mm




ES70/A-06

sliding system with thermal break

ES70


code/description	package/pcs	colour
ET 135408.01		●
ET 135408.02		●
ET 135408.04		○

Pile weatherseal
4P 8.0mm




ET 135414.01		●
ET 135414.02		●
ET 135414.04		○

Pile weatherseal
4P 14.0 mm




ET 135506.01		●
ET 135506.02		●
ET 135506.04		○

Pile weatherseal
FP 6.0mm



ET 135508.01		●
ET 135508.02		●
ET 135508.04		○

Pile weatherseal
FP 8.0mm




sliding system with thermal break

ES70


code/description	package/pcs	colour
ET 135514.01		●
ET 135514.02		●
ET 135514.04		○

Pile weatherseal
FP 14.0 mm




ET 135588.02

Pile weatherseal with
base 4.8 mm, 4P 8 mm
for screen sash E6270220




ET 080701.00

Additional insulator 22x9mm
for frames



ET 080702.00

Additional insulator
16.5x26.6mm for sash wings





sliding system with thermal break

ES70



code/description	package/pcs	colour
ET 080703.00		

Additional insulator
26.4x61mm for hotel mullion





ET 080705.00

Additional insulator 14x12 mm
for hotel frame & adjoining
profile





ET 080706.00

Additional insulator
59x66.3mm for sash interlock
area



ET 080707.00

Additional insulator
60x20mm for hotel mullion





ES70 A-09

sliding system with thermal break

ES70


code/description	package/pcs	colour
ET 080711.00		

Additional insulator
22x15.4mm for frames &
sash





ET 080708.00		
--------------	--	--

Additional insulator
65.7x10.2mm for frames



ET 080709.00		
--------------	--	--


Additional insulator
44x45.5mm for sash



ATTENTION: APPLICABLE
ONLY IN CASE THAT SASH
E6270201 IS FIXED

ET 240711.00		
--------------	--	--

EPDM foam insert for frame
cavities (15mm thick.)



sliding system with thermal break

ES70



code/description	package/pcs	colour
ET 240712.00		

EPDM foam insert for frame
cavities (15mm thick.)




ET 240713.00		
--------------	--	--

EPDM foam insert for frame
cavities (15mm thick.)





ET 240714.00		
--------------	--	--

EPDM foam insert for frame
cavities (15mm thick.)



ET 240715.00		
--------------	--	--

EPDM foam insert for frame
cavities (15mm thick.)



sliding system with thermal break

ES70

code/description	package/pcs	colour
ET 240716.00		


EPDM foam insert for frame cavities (15mm thick.)




E6270131

ET 240717.00		
--------------	--	--

EPDM foam insert for frame cavities (15mm thick.)




E6270130



E6270131

ET 076679.00		
--------------	--	--

EPDM side flange for double & triple flat rails




E6270130 & E6270132



E6270130 remove this part for double rail

ET 076701.00		
--------------	--	--

EPDM side flange for double flat rail with fly screen



E6270130 & E6270132


ES70 A-012

sliding system with thermal break

ES70

code/description	package/pcs	colour
ET 056607.00		inox
ET 057705.00		polyamid 6.6

Alignment square for ES70, E19, E22, E50, E52




E22214

ET 055510.00		galv.steel
ET 055511.00		inox

Alignment square for sash E22214, E 19215

ET 053306.00		silver
--------------	--	--------


Die cast aluminium corner joint bracket for E19, E22



E22214

ET 053316.00		silver
--------------	--	--------

Die cast aluminium corner joint bracket




ES70 A-013

sliding system with thermal break

ES70

code/description	package/pcs	colour
ET 054255.00		MF
ET 054253.00		MF


Extruded aluminium joint
corner bracket - 24.7mm
without hole/with hole



attention
always use epoxy resin
for long lasting joining

ET 052213.00		MF
--------------	--	----

Extruded aluminium corner
joint for sash




ET 057721.00		
--------------	--	--

Alignment corner for sash



ET 054441.00		MF
--------------	--	----

Assembly corner for glazing
sash




sliding system with thermal break

ES70


code/description	package/pcs	colour
ET 054447.00		MF

Extruded aluminium corner
joint for sash




ET 054138.00		MF
--------------	--	----

Extruded aluminium corner
joint for hotel type




ET 058005.00		MF
--------------	--	----

Alignment corner for sash



ET 056604.00		inox
--------------	--	------


Alignment square (5x1.25)




sliding system with thermal break**ES70**

code/description	package/pcs	colour
ET 240427.00		silver

Single roller for fly screen sash ("U" rail)




ET 240428.00		silver
--------------	--	--------

Single roller for fly screen sash (flat rail)


ET 074786.00		●
--------------	--	---

Plastic bottom plug for interlock




ET 074806.00		●
--------------	--	---

Plastic top plug for interlock

**sliding system with thermal break****ES70**


code/description	package/pcs	colour
ET 074811.00		●

Pair of plastic plugs for interlock




ET 074822.00		●
--------------	--	---

Plastic cap for PVC profile of slim interlock (pair)




ET 074824.00		●
--------------	--	---

Central sealing plugs for opposed sashes (pair)



ET 074825.00		●
--------------	--	---


Central sealing plugs for opposed sashes with flat rail (pair)

sliding system with thermal break

ES70


code/description	package/pcs	colour
ET 074471.00		●

Bottom interlock plug for flat rail




ET 074819.00

Roller spacers kit for flat rail




ET 240818.00

Foam part for sealing sash - interlock on top for ES70 hotel type



ET 240835.00

Top foam part for sealing ES70 sash - interlock





sliding system with thermal break

ES70



code/description	package/pcs	colour
ET 240836.00		●

Top foam part for sealing ES70 sash - Slim interlock





ET 240837.00

Central bottom sealing block for ES70 interlock





ET 240838.00

Central bottom sealing block for ES70 Slim interlock



ET 240851.00

Central bottom sealing block for ES70 hotel type




sliding system with thermal break

ES70


code/description	package/pcs	colour
ET 240857.00		●

Central bottom sealing block
for ES70 hotel type (slim
interlock)




ET 240852.00		●
--------------	--	---

Bottom central sealing for
flat rail




ET 240853.00		●
--------------	--	---

Bottom central sealing for
flat rail (for slim interlock)



ET 074831.00		●
--------------	--	---

Stopper for flat rails fly
screen




E6270220
ES70.A-020

sliding system with thermal break

ES70


code/description	package/pcs	colour
ET 074308.00		●

Drainage cap for fly screen
rail




ET 074605.00		●
--------------	--	---

Plastic drainage cap 30x6mm




ET 074309.00		●
--------------	--	---

Open drainage plug for rails
E6270103 & E6270104



ET 074826.00		●
--------------	--	---

Open drainage plug for Hotel
type rail




sliding system with thermal break

ES70


code/description	package/pcs	colour
ET 074830.00		●

Open drainage 35x10mm
for triple & multiple rails




ET 074305.00		●
--------------	--	---

Drainage cap with flap




ET 074743.00		●
--------------	--	---

Plastic plug for fixing hole
covering



ET 074916.00		●
--------------	--	---

Pair of plastic plugs
for E22214





ES70/A-022

sliding system with thermal break

ES70

code/description	package/pcs	colour
ET 074827.00		




Glazing sash safety for
flat rail



E6270201



ET 240423.00	1	
--------------	---	--

Spacer for fixed frame




ET 071498.02		●
--------------	--	---

Aluminium reinforcement for
pvc interlock



ET 074828.00		MF
--------------	--	----

Aluminium rail reinforcement




ES70/A-023

sliding system with thermal break

ES70


code/description	package/pcs	colour
GU 201055.00	1	MF

Connecting rod 8 mm
(for Sash W. 700 - 1600 mm)




code/description	package/pcs	colour
GU 201058.00	1	MF

Connecting rod 8 mm
(for Sash W. 1601 - 1850 mm)




code/description	package/pcs	colour
GU 201059.00	1	MF

Connecting rod 8 mm
(for Sash W. 1851 - 2350 mm)



code/description	package/pcs	colour
GU 201056.00	1	MF

Connecting rod 8 mm
(for Sash W. 2351 - 3300 mm)




ES70.A-024

sliding system with thermal break

ES70


code/description	package/pcs	colour
GU 205108.00	1	MF

Screw M6x75 mm, DIN 965




GU 205109.01	1	●
GU 205109.02	1	●
GU 205109.03	1	brown
GU 205109.11	1	silver

Flush pull 934




GU 205118.00	1	
--------------	---	--

Additional part for GU 934
18 mm



GU 250100.01	1	●
GU 250100.03	1	brown
GU 250100.11	1	silver

Flush pull 934 without
cylinder bore with screw
base plate




sliding system with thermal break

ES70


code/description	package/pcs	colour
GU 250102.01	1	●
GU 250102.02	1	●
GU 250102.03	1	brown
GU 250102.11	1	silver

Flush pull 934 without cylinder bore




GU 250111.01	1	
--------------	---	--

Cover rail extension for gear GU 934, 500 mm




GU 250114.01	1	●
GU 250114.02	1	●
GU 250114.11	1	silver

Sash stopper for GU934/937



GU 250181.01	1	●
GU 250181.03	1	brown
GU 250181.11	1	silver

Removable handle 934



ES70 A-026

sliding system with thermal break

ES70


code/description	package/pcs	colour
GU 250125.01	1	●
GU 250125.03	1	brown
GU 250125.11	1	silver

Rosette for 934 handle without cylinder bore




GU 250129.00	1	
--------------	---	--

Outer rosette for 934 handle




GU 250134.00	1	
--------------	---	--

Rollers GU 934



GU 250140.01	1	●
GU 250140.03	1	brown
GU 250140.11	1	silver

Both side handle 934, with cylinder hole




ES70 A-027

sliding system with thermal break**ES70**


code/description	package/pcs	colour
GU 250119.00	1	

Ventilation striker for hardware 934




GU 250146.00	1	
--------------	---	--

Bottom spacer 18 mm for GU 934




GU 250148.00	1	
--------------	---	--

Additional rollers basic kit for GU 934



GU 250145.11	1	
--------------	---	--

Gear for GU 934 Silver for height 1865 - 2365 mm

**sliding system with thermal break****ES70**


code/description	package/pcs	colour
GU 250149.11	1	

Gear for GU 934 Silver for height 865 - 1285 mm




GU 250150.11	1	
--------------	---	--

Gear for GU 934 Silver for height 1235 - 1865 mm




GU 250151.11	1	
--------------	---	--

Gear for GU 934 Silver for height 2155 - 2765 mm



GU 250696.00	1	
--------------	---	--

Gear extension with locking point EV1




sliding system with thermal break

ES70


code/description	package/pcs	colour
GU 250147.00	1	

Frame striker for GU 934




GU 250900.00	1	
--------------	---	--

Elastic interlock stopper
for GU 934



ET 074773.00		
--------------	--	--

Water drainage valve
Ø8.0 mm



ET 074774.00		
--------------	--	--

Water drainage valve
Ø12.0 mm





ES70 A-030

sliding system with thermal break

ES70

code/description	package/pcs	colour
ET 074840.00		



Pair of end caps for
profile E6270520 - for
90° corner



E6270520

ET 057722.00		
--------------	--	--



Alignment corner for
double or triple rail
(for 90° corner)



E6270103

ET 130729.00		
--------------	--	--


EPDM seal gasket
for 90° corner



E6270520

ET 055053.00		MF
--------------	--	----


Anchor for E6270520
with latch
(for 90° corner)



ES70 A-031


sliding system with thermal break**ES70**

code/description	package/pcs	colour
ET 138001.00		transparent
ET 138001.01		white
ET 138001.02		black
ET 138001.03		brown
ET 138001.04		grey




Silicone for general use 280ml

ET 138000.01		
--------------	--	--




Acrylic putty 280ml

ET 138004.00		
--------------	--	--

One part adhesive (for crimping machine)
with a rapid vulcanisation 290ml

ET 133002.00		
--------------	--	--


Self-adhesive, self-expand tape
'SUPERSEAL 80' for watertightness
and sound insulation (4/20x20)

ES70/A-032

sliding system with thermal break**ES70**

code/description	package/pcs	colour
ET 162269.00		

Punching machine for ES70



--	--	--

--	--	--

ES70/A-033

CE MARKING

STANDARDS / PERFORMANCE CHARACTERISTICS

CE MARKING

WHAT DOES THE SIGN CE MEAN?

It is an abbreviation of the French "Conformite Europeene"- i.e. European Conformity. By placing the CE marking the manufacturer declares that the product complies with the general safety requirements set out in the Construction Product Regulation 305/2011.

WHAT IS THE PURPOSE OF CE MARKING?

The CE marking represents "the European passport" of the product, its main objectives are:

CE is a declaration by the manufacturer that the product meets the essential requirements of relevant European legislation relating to health, safety and environmental protection;

CE indicates to officials in relevant ministries and departments that the product can be put on the market lawfully in the country;

CE ensures free movement of goods within the EU and the European Free Trade Association (EFTA);

CE permits the withdrawal of products that do not meet the standards by monitoring and custom authorities; marking with the CE mark is necessary in cases where the product is distributed within the internal market.

WHAT ARE THE REQUIREMENTS FOR THE CE MARKING?

Doors, windows and gates (except those intended to be used for internal communication only, for fire/smoke compartmentation and on escape routes) are covered by System 3 of assessment and verification of constancy of performance.

According to the Construction Product Regulation 305/2011, this system sets the following duties:

Tasks to be performed by the manufacturer	Tasks to be performed by Notified testing laboratory	Conformity assessment (the basis for CE marking, which is set by the final producer)
factory production control - FPC	Determination of the product type on the basis of type testing, type calculation, tabulated values, etc.	Declaration of performance issued by the manufacturer or his authorized representative based on test results.

LEGAL ACTS

- Construction Products Regulation (305/2011/EU – CPR) – replacing the Construction Products Directive (89/106/EEC – CPD)
- EN 14351-1:2006+A1:2010 – Windows and doors – Product standard, performance characteristics – Part 1: Windows and external pedestrian doorsets without resistance to fire and/or smoke leakage characteristics

MAIN METHODS FOR OBTAINING TEST RESULTS BY THE MANUFACTURER

According to the Construction Product Regulation 305/2011 there are three main options for the manufacturers of windows and doors to obtain test results.



STANDARDS

GENERAL


- EN 12020 (1÷2) – ALUMINIUM AND ALUMINIUM ALLOYS – EXTRUDED PRECISION PROFILES IN ALLOYS EN AW-6060 AND EN AW-6063
- EN 755 (1÷9) – ALUMINIUM AND ALUMINIUM ALLOYS – EXTRUDED ROD/BAR, TUBE AND PROFILES
- EN 573 (1÷3) – ALUMINIUM AND ALUMINIUM ALLOYS – CHEMICAL COMPOSITION AND FORM OF WROUGHT PRODUCTS
- EN 1990 EUROCODE – BASIS OF STRUCTURAL DESIGN
- EN 1991 EUROCODE 1 – ACTIONS ON STRUCTURES
- EN 1998 EUROCODE 8 – DESIGN OF STRUCTURES FOR EARTHQUAKE RESISTANCE
- EN 1999 EUROCODE 9 – DESIGN OF ALUMINIUM STRUCTURES

WINDOWS AND DOORS

1. EN 14351 – WINDOWS AND DOORS – PRODUCT STANDARD, PERFORMANCE CHARACTERISTICS
2. EN 12519 – WINDOWS AND PEDESTRIAN DOORS – TERMINOLOGY
3. EN 12207 – WINDOWS AND DOORS – AIR PERMEABILITY – CLASSIFICATION
4. EN 1026 – WINDOWS AND DOORS – AIR PERMEABILITY – TEST METHOD
5. EN 12208 – WINDOWS AND DOORS – WATERTIGHTNESS – CLASSIFICATION
6. EN 1027 – WINDOWS AND DOORS – WATERTIGHTNESS – TEST METHOD
7. EN 12210 – WINDOWS AND DOORS – RESISTANCE TO WIND LOAD – CLASSIFICATION
8. EN 12211 – WINDOWS AND DOORS – RESISTANCE TO WIND LOAD – TEST METHOD
9. EN 1191 – WINDOWS AND DOORS – RESISTANCE TO REPEATED OPENING AND CLOSING – TEST METHOD
10. EN ISO 10077 (1÷2) – THERMAL PERFORMANCE OF WINDOWS, DOORS AND SHUTTERS – CALCULATION OF THERMAL TRANSMITTANCE
11. EN 12412-2 – THERMAL PERFORMANCE OF WINDOWS, DOORS AND SHUTTERS – DETERMINATION OF THERMAL TRANSMITTANCE BY HOT BOX METHOD – PART 2: FRAMES
12. EN 13115 – WINDOWS – CLASSIFICATION OF MECHANICAL PROPERTIES – RACKING, TORSION AND OPERATING FORCES
13. EN 1627 – WINDOWS, DOORS, SHUTTERS – BURGLAR RESISTANCE – REQUIREMENTS AND CLASSIFICATION
14. EN 1628 – WINDOWS, DOORS, SHUTTERS – BURGLAR RESISTANCE – TEST METHOD FOR THE DETERMINATION OF RESISTANCE UNDER STATIC LOADING
15. EN 1629 – WINDOWS, DOORS, SHUTTERS – BURGLAR RESISTANCE – TEST METHOD FOR THE DETERMINATION OF RESISTANCE UNDER DYNAMIC LOADING
16. EN 1630 – WINDOWS, DOORS, SHUTTERS – BURGLAR RESISTANCE – TEST METHOD FOR THE DETERMINATION OF RESISTANCE TO MANUAL BURGLARY ATTEMPTS
17. EN ISO 717-1 – ACOUSTICS – RATING OF SOUND INSULATION IN BUILDINGS AND OF BUILDING ELEMENTS – PART 1: AIRBORNE SOUND INSULATION
18. EN ISO 10140 – ACOUSTICS – LABORATORY MEASUREMENT OF SOUND INSULATION OF BUILDING ELEMENTS

HATCHES

Hatches for different materials



LIABILITY

The stated data and calculating methods are provided by ETEM as a guideline only. The information given in this catalogue does not substitute of all applicable regulations – Eurocodes, harmonized European standards, national or regional building codes.

The specific conditions and technical details of every particular project have to be taken into consideration.

The right choice of all elements as well as any special requirements regarding stability of the structure must always be considered by the structural/façade engineer, responsible for the project.

The solutions presented in these pages are indicative and can not cover all possible project cases. Because of that every single project has to be evaluated by the structural/façade engineer in charge taking into consideration the specific features, such as climate conditions, location, orientation, etc.

ETEM is not liable for any calculations and conclusions made on the basis of the stated information. All calculations and specifications must be estimated, endorsed and guaranteed by architect, engineer, professional or legal entity authorized by law for such activities.

COPYRIGHT

Copyright© II EDITION 2021 ETEM


The design, structure and content of this catalogue are subject of copyright and the exclusive rights belong to ETEM. Modifying, copying, publishing, selling or licensing any part or the whole content of this catalogue are strongly prohibited without the permission of ETEM. Any unauthorized use of content may violate copyright or other laws.

DISCLAIMER

ETEM is not responsible for any typographical errors, technical inaccuracies and following changes of the content of this catalogue.

Before starting manufacturing process, it is highly recommended to contact ETEM R&D department in order to provide you with updated information.





WWW.ETEM.COM

ETEM